



定格総荷重表

ショートジブ装着

単位: トン

作業半径 (m)	ブーム長さ (m)							
	15.0	18.0	24.0	30.0	36.0	39.0	45.0	51.0
5.3	149.5							
6.0	139.5	137.5						
6.5	134.5	132.5						
7.0	129.5	127.5	7.3m/115.5					
8.0	114.5	112.5	105.5	8.7m/95.5				
9.0	97.6	97.2	96.5	93.1				
10.0	83.6	83.2	82.7	82.3	81.8	10.7m/74.0		
12.0	64.7	64.3	63.7	63.2	62.9	62.8	62.3	13.4m/52.9
14.0	52.6	52.1	51.5	51.0	50.6	50.5	50.0	49.7
16.0	15.6m/41.7	43.7	43.0	42.5	42.1	41.9	41.5	41.1
18.0		17.2m/39.0	36.8	36.2	35.8	35.7	35.2	34.8
20.0			32.0	31.4	31.0	30.8	30.3	29.9
22.0			28.3	27.7	27.2	27.0	26.5	26.1
24.0			22.4m/27.7	24.6	24.1	23.9	23.4	23.0
26.0				22.1	21.6	21.4	20.9	20.4
28.0				27.6m/20.4	19.5	19.3	18.7	18.3
30.0					17.7	17.4	16.9	16.4
32.0					16.1	15.9	15.3	14.8
34.0					32.8m/15.6	14.6	14.0	13.5
36.0						35.4m/13.7	12.8	12.3
38.0							11.7	11.2
40.0							10.8	10.3
42.0							40.6m/10.6	9.5
44.0								8.7
45.8								8.1
ブーム傾斜角の範囲	20° ~ 77°	30° ~ 77°						

2017年 9月改訂

船名	大光2000		
船種	クレーン付台船		
形式	スパット式(18mx2)		
規格	200t吊 ブーム長: 51.0m		
図番	A3	縮尺	1:150
大光建設株式会社			